

VS Safety is a world-leading provider of wireless security and home automation solutions. Our company is well recognized for the track record of technological innovations and for the high quality of our products.



Accessories

Introduction

The **Universal Receiver UR-7 & 8** is specially designed to make all existing control panels compatible with other external appliances. The UR is a wireless output module that can be connected to a broad variation of appliances.

The Universal Receiver provides a relay output for the following alarms and conditions:

- Arm – Disarm • Fire Alarm • Remotely operated (SMS/WEB)
- Burglary alarm • Water Alarm • Tamper Alarm

Each alarm type/event can be programmed to NO/NC relay option modes. There is no limitation on numbers of UR modules connected to an alarm system



Specifications

Power Supply: 12V DC
Current Consumption: idle: 0; RF Transmission: 27mA
Radio frequency: 868 (UR-8) or 433 MHz (UR-7)

Output: Relay Dry Contact
Output Mode: Latch / Pulse, programmable
Relay Output Type: Normal Open / Normal Close, programmable
Relay Contact Capacity: 0.5A 125V AC or 1A 30V DC
Operation Range: 300m in open space.
Temperature Range: -10C ~ +50C
Humidity: up to 85%
Dimension: 100mm (L) x 57mm (W) (max.) x 22.2mm (H) (max.)