

The 1350/1360 series is a range wall mounted electromagnetic door retainers that offers the user a choice of holding strengths.

Robust and simple to install, they are ideal for a wide range of applications such as nursing homes, hospitals, schools and industrial premises. Doors can be held open under normal conditions and then automatically released in the event of a fire alarm activation.


Features

- Versatile holding settings
- High holding force
- Low current consumption
- Release button and protection circuit
- Adjustable damping keeper plate
- Protection diodes as standard

Benefits

- Flexibility in installation
- Suitable for large and small fire doors
- Requires less power from your system
- Door can be manually closed when not activated by the fire system
- Allows for door misalignment

Dimensions







Technical Specification

Holding Force	25-50Kg 245-490N /50-100Kg 490-960N	
Voltage	24Vdc	
Current	25-45mA / 40-100mA	
Mounting	Wall mounting / Floor bracket available	
Housing Material	Steel / ABS cover	
Temperature Range	10°C to +55°C	
Protection	IP40	
Weight	800g / 1000g	
Body Colour	White / Black	

Catalogue Numbers

Reference	Cat No	Description
FSMD/024/40/W/DIODE	1350-CSA	Wall Mounted Magnetic Door Release 24Vdc, 40Kgf/390N (includes diode protection circuit)